



PONTES ROLANTES



Schwanke
Movimentação de Cargas

PONTE ROLANTE DUPLA VIGA

Capac. T	A*	B	C	D	E	F	G	H	I	R máximo	R mínimo
	mm	mm	mm	mm	mm	mm	mm	mm	mm	kgf	kgf
5	8	2400	2930	530	610	610	960	6000	150	2900	655
	12	2800	3330	530	610	610	960	6000	150	3230	820
	16	3200	3730	530	610	610	960	6000	200	3520	1050
	20	3200	3730	530	610	610	960	6000	200	3950	1420
	24	3400	3930	530	610	610	960	6000	200	4350	1800
6,3	8	2400	2930	530	610	610	960	6000	150	3660	780
	12	2800	3330	530	610	610	960	6000	150	3880	870
	16	3200	3730	530	610	610	960	6000	200	4260	1180
	20	3200	3730	530	610	610	960	6000	200	4600	1450
	24	3400	3930	530	610	610	1050	6000	200	5150	2000
8	8	2400	2930	670	610	610	1050	6000	150	4420	860
	12	2800	3330	670	610	610	1050	6000	200	4830	1000
	16	3200	3730	670	610	610	1050	6000	200	5200	1320
	20	3200	3730	670	610	610	1050	6000	200	5650	1670
	24	3400	3930	670	610	610	1050	6000	200	6550	2500
10	8	2400	2930	670	610	610	1050	6000	150	5350	880
	12	2800	3330	670	610	610	1050	6000	200	5800	1150
	16	3200	3730	670	610	610	1050	6000	200	6250	1440
	20	3200	3730	670	610	610	1050	6000	200	6700	1880
	24	3400	3930	670	610	610	1050	6000	200	7560	2600
12,5	8	2400	2930	670	610	610	1100	6000	150	6800	1330
	12	2800	3330	670	610	610	1100	6000	200	7400	1460
	16	3200	3730	670	610	610	1100	6000	200	7950	1800
	20	3200	3730	670	610	610	1100	6000	200	8400	2210
	24	3400	3930	670	610	610	1100	6000	200	9340	2990
16	8	2800	3330	740	840	840	1200	6000	200	8480	1540
	12	2800	3330	740	840	840	1200	6000	200	9200	1810
	16	3200	3730	740	840	840	1200	6000	200	9790	2150
	20	3200	3730	740	840	840	1200	6000	200	10500	2670
	24	3400	3930	740	840	840	1200	6000	200	11200	3410
20	8	2800	3330	1000	840	840	1200	6000	200	10400	2050
	12	2800	3330	1000	840	840	1200	6000	200	11100	2100
	16	3200	3730	1000	840	840	1200	6000	200	11800	2410
	20	3200	3730	1000	840	840	1200	6000	200	12600	3000
	24	3400	3930	1000	840	840	1200	6000	200	13300	3510
25	8	2800	3330	860	840	840	1200	6000	200	12900	2700
	12	2800	3330	860	840	840	1200	6000	200	13900	2560
	16	3200	3730	860	840	840	1200	6000	200	14900	2980
	20	3200	3730	860	840	840	1200	6000	200	15700	3440
	24	3400	3930	860	840	840	1200	6000	200	16500	4060
32	8	3200	3830	1000	880	880	1400	6000	200	16000	3230
	12	3200	3830	1000	880	880	1400	6000	200	17300	3480
	16	3200	3830	1000	880	880	1400	6000	200	18600	3730
	20	3200	3830	1000	880	880	1400	6000	200	19600	4360
	24	3800	4450	1000	880	880	1400	6000	200	20900	52200

As pontes rolantes Schwanke são fabricadas segundo as normas BNR 8400, FEM e DIN.

