



PONTES ROLANTES



Schwanke
Movimentação de Cargas

PONTE ROLANTE UNIVIGA

Capac. T	A*	B	C	D	E	F	G	H	I	R máximo	R mínimo
	mm	mm	mm	mm	mm	mm	mm	mm	mm	kgf	kgf
1	4	1600	2030	461	350	350	320	6000	150	655	130
	8	2000	2430	461	350	350	420	6000	150	770	245
	12	2000	2430	461	350	440	440	6000	150	920	395
	16	2400	2830	461	350	440	590	6000	150	1085	560
	20	2800	3230	461	350	530	640	6000	150	1360	830
2	4	1600	2030	619	400	350	370	6000	150	1180	140
	8	2000	2430	619	400	350	440	6000	150	1325	285
	12	2000	2430	619	400	440	590	6000	150	1485	440
	16	2400	2830	619	400	440	640	6000	150	1720	680
	20	2800	3230	619	400	530	745	6000	200	1975	935
3,2	4	1600	2030	700	410	410	415	6000	150	1855	155
	8	2000	2430	700	410	410	540	6000	150	2025	325
	12	2000	2430	700	410	410	590	6000	150	2235	535
	16	2400	2830	700	410	410	745	6000	150	2480	780
	20	2800	3230	700	410	480	845	6000	200	2715	1015
4	4	1600	2030	700	725	725	420	6000	150	2350	160
	8	2000	2430	700	725	725	540	6000	150	2530	340
	12	2000	2430	700	725	725	740	6000	150	2695	505
	16	2400	2830	700	725	725	845	6000	200	3040	850
	20	2800	3230	700	725	725	945	6000	200	3275	1083
5	4	1600	2030	700	725	725	420	6000	150	2580	160
	8	2000	2430	700	725	725	595	6000	150	6110	365
	12	2000	2430	700	725	725	750	6000	150	3240	550
	16	2400	2830	800	725	725	850	6000	200	3565	875
	20	2800	3230	800	725	725	1045	6000	200	3830	1140
6,3	4	1600	2030	700	725	725	450	6000	150	3555	205
	8	2000	2430	700	725	725	645	6000	150	3725	375
	12	2000	2430	700	725	725	845	6000	150	3920	560
	16	2400	2830	800	725	725	945	6000	200	4235	885
	20	2800	3230	800	725	725	1045	6000	200	4620	1270
8	4	1600	2030	800	725	725	450	6000	150	4685	255
	8	2000	2430	800	725	725	650	6000	150	4830	400
	12	2000	2430	800	725	725	850	6000	150	5045	615
	16	2400	2830	900	725	725	955	6000	200	5460	1030
	20	2800	3230	900	725	725	1055	6000	200	5885	1455
10	4	1600	2030	800	725	725	450	6000	150	5700	270
	8	2000	2430	800	725	725	750	6000	150	5865	435
	12	2000	2430	800	725	725	955	6000	200	6090	660
	16	2400	2830	900	725	725	1055	6000	200	6490	1060
	20	2800	3230	900	725	725	1155	6000	200	6950	1520
12,5	4	1600	2030	800	800	800	450	6000	150	7000	302
	8	2000	2430	800	800	800	755	6000	150	7180	480
	12	2000	2430	800	800	800	960	6000	200	7435	735
	16	2400	2830	900	800	800	1155	6000	200	7830	1130
	20	2800	3230	900	800	800	1265	6000	200	8420	1720

* Para outros vãos e alturas consultar. Sujeito a alterações sem aviso prévio.

